

Has "Power" Down-Feed and Improved Power Traverse Controls. Makes Undercutting Faster and Easier than Ever!



- ☛ **Power-Operated: Makes Undercutting Faster and Easier.**
- ☛ **Uses Tungsten-Carbide or High Speed Steel Saws.**
- ☛ **Heavy, Rigid Construction for Industrial Use.**

Specifications:

Handles Armatures:
Up to 44" diameter (this will depend upon relative diameters of armature and commutators. Send us your requirement).
From 150 to 10,000 lbs.

Handles Commutators:
10" to 44" diameter.
Up to 21" length.

Base Length:
Up to 58" between roller supports. Additional length available at slightly higher cost.

Motor:
3/4 h.p.; 3450 r.p.m.
Extra pulley and belt are supplied to give spindle speeds of 3450 r.p.m. for High-Speed Steel Saws or V-Cutters, or 6900 r.p.m. for Tungsten-Carbide Saws or V-Cutters.

Air Supply:
About 90 lbs., controlled by pressure regulator with oiler and filter.

Saws and V-Cutters:
1/2", 7/8", or 1" O.D. Saws or V-Cutters. (See table below.)

Features:

- ☛ **Power Traverse — With Improved Electric Motor Variable Speed-Drive Control**
An improved traverse system powered by an electric motor driven ball screw-drive, actuated by a foot pedal connected to a variable speed drive control. This system provides enhanced smooth vibration free undercutting with minimal maintenance requirements.
- ☛ **Power Down Feed — Hand-Valve Actuated**
Holds the saw in the slot while cutting, lifts it from the slot while returning and indexing.
- ☛ **Magnifier Lamp —**
Illuminates and magnifies work area for accurate and easy saw alignment.
- ☛ **Simple Indexing —**
A hand wheel, connected by a flexible shaft to 100 to 1 speed reducer with a flat belt around the armature, combine to give quick positive indexing with no override or inertia problems. Belt segments of various lengths are furnished to fit any armature. Belt drive may be positioned anywhere along base.
- ☛ **Depth of Cut —**
Fine adjustment is made with hand wheel on top of carriage. Rack and gear on frame are for major adjustments.
- ☛ **Supports —**
Armatures shafts rest and rotate on 4 large phenolic rollers; assures no marking of shafts.
- ☛ **Adjustable Rear Support —**
Vertically (on thrust bearing) for unequal shaft-sizes or tapered commutators. Sideways (on "Teflon" ways) from front of machine - for skewed bars. Length - rear support slides and locks into place to accommodate various armature lengths.
- ☛ **Carriage —**
Slides on "Oilite" bushings over hardened steel rods. Adjustable stops at each end of stroke.
- ☛ **Saw Spindle —**
1-1/2" hardened over-arm supports outer end of spindle. Two spindles available; one for 1/2" diameter saws (3/16" arbor hole) and the other for 7/8" and 1" diameter saws (5/16" arbor hole). Specify which one desired when ordering. An optional 2-position saw spindle block is available (at extra cost) which allows cutting up close to the riser in one position, and up close to a shoulder at the front of the commutator when in the other position.

Dust Collector removes mica dust quickly; comes with two hoods for use in a wide variety of dusty jobs.
Has paddle-wheel type fan driven by 1/3 h.p., 3450 r.p.m. motor. Plugs into outlet box on undercutter.
The Dust Collector is self-contained and easily portable to other locations where dust collection is desirable.



Model HA-2 Undercutter complete:	Catalog Number
115 V., 50/60 Hz., with 3/16" spindle	HA2UA3
115 V., 50/60 Hz., with 5/16" spindle	HA2UA5
230 V., 50/60 Hz., with 3/16" spindle	HA2UB3
230 V., 50/60 Hz., with 5/16" spindle	HA2UB5
Extra 3/16" Saw Spindle Assembly	HA2U43316
Extra 5/16" Saw Spindle Assembly	HA2U43516
Net Weight 750 lbs., Shipping Weight 1,020 lbs.	
Dust Collector with 2 hoods, 115 V., 60 Hz.	DSCLCA
Dust Collector with 2 hoods, 230 V., 50 Hz.	DSCLCB
Net Weight 58 lbs., Shipping Weight 65 lbs.	

Saws and V-Cutters			
High-Speed Steel	O.D.	I.D.	Catalog Number
16-HS Saws	1/2"	3/16"	HSMS16
17-VHS Cutters	1/2"	3/16"	HSMSV17
75-HS Saws	7/8"	5/16"	HSMS75
75-VHS Cutters	7/8"	5/16"	HSMSV75
85-HS Saws	1"	5/16"	HSMS85
85-VHS Cutters	1"	5/16"	HSMSV85
Tungsten-Carbide	O.D.	I.D.	Catalog Number
16-TC Saws	1/2"	3/16"	TUNSV16
17-VTC Cutters	1/2"	3/16"	TUNSV17
75-TC Saws	7/8"	5/16"	TUNSV75
75-VTC Cutters	7/8"	5/16"	TUNSV75
85-TC Saws	1"	5/16"	TUNSV85
85-VTC Cutters	1"	5/16"	TUNSV85

For further specifications see pages 16 and 17.